

SPEED LANE BARRIER



Leading Indian Manufacturer of all types of Pedestrian Access Control System's

SPEED LANE BARRIER



🔧 Technical Specification:

- Supply Voltage : 230VAC \pm 10%
- Power Consumption : 15-80 Watt
- Drive Technology* : BLDC / Stepper Motor Drive
- Communication Protocol* : USB or RS485 or RS232
- Integration* : 4 Inputs, 4 PFC outputs & Optional RS485
- Access Time Out : 0 - 15 sec (Adjustable)
- Opening / Closing Speed : Less than 1 Sec
- Duty Cycle : Intensive use
- Cabinet Material : Available in Stainless Steel Grade 304/316 Or Mild Steel
- Swing Arm material : Toughen Glass* or Polycarbonate
- Cabinet Dimension : L 1300mm * W 200mm * H 1000mm \pm 5%
- Passage Width : 600mm & 900mm (Adjustable)
- Lane Indicator : Built-in (Green or Red)
- Throughput : 30-35 persons/minute
- M.C.B.F. : 10 million cycles
- Operating Temperature : -10 to 55° C
- Installation : By anchor bolts on plain surface
- Included Accessories : Mains Cable, Foundation Bolts etc.
- Optional Accessories : Swing Arm with RGB LED, Digital IN-OUT Counter, Wireless Remote, S.S. Railings, Canopy etc.



SPEED LANE BARRIER



General Arrangement Drawing:

